

### MODELS

Compaq V570 CRT Monitor  
 228114-xxx Opal  
 228113-xxx Carbon/Silver

### SPECIFICATIONS

|  |   |                             |                      |                                  |
|--|---|-----------------------------|----------------------|----------------------------------|
| Tube Type                              | 15 inch (38.1 cm) FST, Shadow Mask                                    |                             |                      |                                  |
| Picture Tube Size (diagonal)           | 15-inch (38.1 cm) Flat Square   |                             |                      |                                  |
| Viewable Image Area (diagonal)         | 13.8 inch (35.1 cm)   |                             |                      |                                  |
| Trio Dot Pitch                         | 0.28 mm   |                             |                      |                                  |
| Horizontal Dot Pitch                   | 0.24 mm   |                             |                      |                                  |
| Horizontal Frequency (kHz)             | 30 to 70 kHz  |                             |                      |                                  |
| Vertical Frequency (Hz)                | 50 to 160 Hz  |                             |                      |                                  |
| Maximum Pre-set Resolution             | 1280 x 1024 @ 65 Hz   |                             |                      |                                  |
| Preset Graphic Modes                   | 1024 x 768<br>@ 60, 75 and 85 Hz                                      | 800 x 600<br>@ 75 and 85 Hz | 720 x 400<br>@ 70 Hz | 640 x 480<br>@ 60, 75, and 85 Hz |
|  | <b>NOTE:</b> All modes are non-interlaced unless specified otherwise. |                             |                      |                                  |
| Mac Compatible Modes                   | Not applicable<br><b>NOTE:</b> Adapter required.                      |                             |                      |                                  |
| User-Programmable/Preset Graphic Modes | 8/8   |                             |                      |                                  |
| Anti-Glare/Anti-Static                 | Yes/Yes   |                             |                      |                                  |
| Plug and Play                          | Yes   |                             |                      |                                  |
| Icon Based On-Screen Display Controls  | Yes   |                             |                      |                                  |
| User Controls                          | Brightness, Contrast  | Yes                         |                      |                                  |
|  | Size and Positioning  | Yes                         |                      |                                  |
|  | Pincushion (barrel)   | Yes                         |                      |                                  |
|  | Trapezoid   | Yes                         |                      |                                  |
|  | Tilt (rotation)   | Yes                         |                      |                                  |
|  | Color temperature   | Yes                         |                      |                                  |
|  | Parallelogram   | Yes                         |                      |                                  |
|  | Pincushion Balance  | Yes                         |                      |                                  |
|  | Individual color control  | No                          |                      |                                  |
|  | Moiré Cancellation  | Yes                         |                      |                                  |
|  | Convergence   | No                          |                      |                                  |
|  | Overscan  | No                          |                      |                                  |

## SPECIFICATIONS *(continued)*

|   |   |     |
|---|---|-----|
| <b>User Controls</b> <i>(continued)</i> | <b>Serial Number Display</b>                          | No  |
|   | <b>Power Saver (on/off)</b>                           | No  |
|   | <b>Display Mode</b>                                   | Yes |
|   | <b>Degauss</b>  | Yes |
|   | <b>Factory Recall</b>                                 | Yes |
|   | <b>OSD Lock / Unlock</b>                              | Yes |
|   | <b>Zoom</b>   | Yes |
|   | <b>Video Input Level</b>                              | Yes |
| <b>Approvals/Certifications</b>         | <b>UL Approval</b>                                    | Yes |
|   | <b>ISO9241-3, ISO9241-7, ISO9241-8 VOT Guidelines</b> | Yes |
|   | <b>MPR-II Compliant</b>                               | Yes |
|   | <b>FCC Approval</b>                                   | Yes |
|   | <b>Energy Star Compliant</b>                          | Yes |
|   | <b>TCO 99 Compliant</b><br>(select models)            | Yes |
| <b>Language Selection</b>               | English   |     |
|   | German  |     |
|   | French  |     |
|   | Spanish   |     |
|   | Italian   |     |
|   | Portuguese  |     |
|   | Russian   |     |
|   | Korean  |     |
| Swedish                                 |   |     |
| <b>Maximum Pixel Clock Speed</b>        | 94.5 MHz (maximum)                                    |     |
| <b>Maximum Power Rating</b>             | 75 Watts  |     |
| <b>Power Supply ALS</b>                 | Universal/Auto-Sensing; 100 to 240 VAC                |     |
| <b>Power Saving Mode</b>                | < 3W  |     |
| <b>Synch Input</b>                      | TTL separate synch                                    |     |
| <b>Signal Cable</b>                     | 15-pin miniature D-sub                                |     |
| <b>Tilt Base (up/down)</b>              | 10° up, 5° down                                       |     |
| <b>Swivel</b>                           | ± 45° of center                                       |     |

### SPECIFICATIONS *(continued)*

|  |  |   |
|--|--|---|
| <b>Intelligent Manageability</b>           | AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability and appropriate network software   |   |
| <b>USB Capabilities</b>                    | No   |   |
| <b>Input Impedance</b>                     | 75 ohms  |   |
| <b>Dimensions (H x W x D)</b>              | <b>Unpacked</b>  | 14.5 x 14.0 x 14.9 in/36.9 x 35.6 x 37.9 cm   |
|  | <b>Packaged</b>  | 17.28 x 18.26 x 18.8 in/43.9 x 46.4 x 47.8 cm |
| <b>Weight</b>                              | <b>Unpacked</b>  | 26.2 lb/11.79 kg                              |
|  | <b>Packaged</b>  | 30.36 lb/13.8 kg                              |
| <b>Operating Temperature</b>               | 32° to 104°F/0° to 40°C  |   |
| <b>Operating Humidity (non-condensing)</b> | 10% to 80%   |   |
| <b>Limited Warranty</b>                    | One year Worldwide warranty standard. If this monitor fails during the parts warranty, Compaq guarantees that a new, or like-new monitor replacement will be delivered within 48 hours.<br><b>NOTE:</b> Certain restrictions and exclusions apply. Consult the Compaq Customer Service Support Center for details. |   |

### COMPATIBILITY

|                         |   |
|-------------------------|---|
| <b>Video Controller</b> | ATI RAGE PRO Turbo 2X<br>Diamond Velocity 4000<br>Diamond Viper V730<br>Diamond Viper V770 Ultra<br>ELSA GLoria II<br>ELSA Synergy II<br>Intel 810<br>Intel 810E<br>Intel 815<br>Matrox G200 Quad Multi-Monitor Series<br>Matrox Millennium G200<br>Matrox Millennium G400 DualHead<br>Matrox Millennium G400 Digital Video Interface (DVI) Daughter Board<br>Matrox Millennium G400<br>Matrox Millennium G450<br>Matrox Millennium II<br>NVIDIA GeForce 256<br>NVIDIA GeForce 2 GTS<br>NVIDIA TNT2 M64<br>NVIDIA TNT2 Pro<br>NVIDIA Vanta<br>S3 VIRGE/MX |
|-------------------------|---|

Compaq, registered United States Patent and Trademark Office. Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.

©2002 Compaq Computer Corporation.